Agrivoltaics 101



New Jersey Agricultural Experiment Station


Both


Extension Specialist

RUTGER



Rutgers Agrivoltaics Program





<u>Agrivoltaics</u> (a.k.a. dual-use solar) simultaneously combines agriculture/horticulture with solar energy generation on the same piece of land

Keeps the land in agricultural production
 Contributes to the state's renewable energy mandate

Different types of agrivoltaic systems

Fixed-tilt (low to the ground, South facing)

Seasonally adjustable tilt (manual, on posts, South facing)

Single-axis trackers (North-South rows, various post heights)

Dual-axis trackers (always pointed perpendicular to the Sun)

Vertical bifacial (no moving parts, bifaciality factor)

Elevated fixed-tilt or trackers on support structures

Fixed-tilt, South facing

Ben Moreell Solar Farm Naval Weapons Station Earle Tinton Falls, NJ Little room for agriculture: > Sheep grazing > Pollinator habitat

Seasonally adjustable tilt, South facing

Middlesex County EARTH Center South Brunswick, NJ

Single-axis trackers with single rows of panels (1P) Rows oriented North – South

Snyder Farm, Pittstown, NJ

Single-axis trackers with double rows of panels (2P) Rows oriented North – South

RAREC, Upper Deerfield, NJ

Dual-axis trackers, always pointed to the Sun



Vertical bifacial (VBF) with North – South rows

Cook Campus Animal Farm

New Branswick NJ

Nu con reum

Elevated agrivoltaics with single-axis trackers



Snyder Farm, Pittstown, NJ






95 kW_{DC} installed, 82.4 kW_{DC} grid-connected, single-axis trackers with a pivot point 2.4 m (8 feet) above ground level): hay production. Two treatment blocks, each with a control area and five rows with single rows of panels. Row spacing: 9.8 m (32 feet).

RAREC, Upper Deerfield, NJ





255 kW_{DC} installed, 48.6 kW_{DC} grid-connected, single-axis trackers with a pivot point 2.4 m (8 feet) above ground level: Staple and vegetable crop production. Three randomized blocks, each with a control area, three rows with single rows of panels, and three rows with double rows of panels. Row spacing: 10.4 m (34 feet).

Animal Farm, New Brunswick, NJ



Vertical bifacial panels



170 kW_{DC}: Grazing large animals and forage production. Three randomized blocks, each with a control area, three rows with 61 cm (2 feet) clearance height, and three rows with 1.22 m (4 feet) clearance height. Row spacing: 6.1 or 12.2 m (20 or 40 feet). Each row has 21 vertical bifacial panels (oriented East or West).

Key lessons learned/challenges encountered

- Every electric utility has its own procedures/timelines
 The local grid capacity may not be large enough
 Grid capacity information is not always easy to obtain
 Grid upgrades are very expensive and time-consuming
 Price per watt for each system (For our VBF > \$4/W_{DC})
 Consider trackers that can rotate ±90° from horizontal
 East or West orientation of VBF panels?
- Need for contingency funds (be aware of rocky fields)
- Design-build projects require good communication and trust between developer and customer
- Operating large agricultural equipment near an agrivoltaic system can be tricky and will likely slow the process down

Operating equipment near agrivoltaic systems









General design and construction challenges

- Few design tools available for agrivoltaics
- > Hiring an experienced developer/contractor
- Keeping the developer/contractor focused on agriculture
- > Time required to get permits/approvals
- Dealing with delays in the supply chain
- Planning for future replacement/decommissioning
- Projects can be more time consuming than anticipated



Specific construction challenges



Soil compaction

Handling topsoil

Post refusals



Conduit risers



Placement of conduit boxes



New Jersey Agricultural Experiment Station

Thank your Questions: A.J. Both



both@sebs.rutgers.edu